

Shed Delivery Instructions

We require,

- Clearance height of approximately 15ft.
- Width clearance of 2ft wider than your shed(if the building is 16ft wide we need 18ft).
- A driveway or path that meets all conditions above. If not we may not be able to deliver on schedule, depending on ground conditions.
- If gates are present they must be 12in+ wider than the width of the shed.
- If there are any steep hills, sharp turns, or creeks to cross please send us a short video clip of the route as you drive through with a vehicle or a UTV. Starting at the beginning of the road all the way to the site.
- Room to maneuver a truck/trailer

-All changes must be approved before construction begins. Any changes made after construction has begun may result in an additional charge.

-Please take a moment before you order your barn. Can we get to the site? Which way do you want the shed facing?

-Any shed over the size of 12x32 we recommend concrete footers. If you proceed without footers, your warranty will not cover any settling issues.(Also note we recommend using our basic shed doors if no footers are present).

-If you want a footer plan please ask a Hilltop sales person, they will be happy to send you the plan.

-Try to find a level spot for your shed, a steep grade is not recommended, but we will level the building with cinder blocks the best we can up to 36in high.

- If you have any questions about delivery, please ask to speak with Dave or Josh to discuss delivery options, the best route to follow.

Call: 615-789-0062

Thank you for your cooperation!

~The Delivery Crew

